



HDPE dual-wall  
drainage piping systems

- 25 year warranty
- full on-site technical support
- 24-hour support hotline



At CMF we've been developing a reputation that's founded on one simple thing: integrity. It's how we approach our products, it's how we treat our customers, it's how we do business. Look for our CorrDrain brand to ensure that your pipe has been engineered with integrity.

#### CorrDrain™ FEATURES & BENEFITS:

- Engineered blend of high density polyethylene material containing 50% minimum recycled content
- Watertight integral bell and spigot coupling system
- Bell and spigot is verified to ASTM D3212 10.8 psi laboratory test
- Manning's "n" value of 0.012
- Lightweight, easy to handle, and easy to cut in the field
- Full offering of standard and custom fittings
- HDPE material is completely resistant to rusting, corrosion and deterioration
- High performance green product ideally suited for green projects
- Bell and spigot allows for quick and easy installation reducing costs while increasing efficiency
- Watertight validation helps to ensure field performance with reduced joint infiltration/exfiltration
- Low Manning's value allows for greater flow capacity and reduces sediment or debris build-up
- Lightweight and easy field manipulation saves time, labor, and allows for the use of smaller equipment
- Fittings to meet your specific needs and reduce field fabrication and costly structures

CorrDrain is high density polyethylene plastic pipe containing a minimum of 50% recycled HDPE with finished product and material performance exceeding the requirements of AASHTO M294 or ASTM F2306. It is the ideal choice for high-volume watertight gravity-flow drainage applications – especially where an environmentally-conscious product is demanded. CorrDrain is also manufactured to meet ASTM D3212 watertight laboratory test requirements.



CorrDrain™ by CMF GLOBAL

2445 Fenton Street ■ Chula Vista, CA 91914-3517 ■ Telephone: 619-869-8919 ■ Fax: 619-330-4532

1-877-586-6060 24 Hour Technical Hotline ■ 25 YEAR LIMITED SYSTEM WARRANTY

PRODUCT INSTALLATION TRAINING AVAILABLE

 **CMF**  
by GLOBAL

[www.corrdrain.com](http://www.corrdrain.com)



- 25 year warranty
- full on-site technical support
- 24-hour support hotline

**CorrDrain™ applications\*:**

- Storm Sewer
- Highway Drainage
- Parking Lot Drainage
- Storm Water Detention Systems
- Industrial Applications
- Ditch Enclosures

\* Contact your CMF representative regarding application suitability questions.



**CorrDrain™ pipe meets the following industry standards:**

- ASTM F 2306: Standard Specification for 12" - 60" (300 - 1500 mm) Annular Corrugated Profile-Wall Polyethylene (PE) Pipe and Fittings for Gravity-Flow Storm Sewer and Subsurface Drainage Applications\*
- AASHTO M 252: Standard Specification for Corrugated Polyethylene Drainage Pipe\*
- AASHTO M 294: Standard Specification for Corrugated Polyethylene Pipe, 300 - 1500 mm Diameter\*
- ASTM F 477: Standard Specification for Elastomeric Seals (Gaskets) for Joining Plastic Pipe
- ASTM D 3212: Standard Specification for Joints for Drain and Sewer Plastic Pipes Using Flexible Elastomeric Seals

\* CorrDrain meets the material and finished product performance requirements of this standard and is manufactured with a minimum of 50% recycled content.



**AVAILABLE SIZES:**

Diameter	Number	Nominal Length
4"	CD4EF20NP	20'
6"	CD6EF20NP	20'
8"	CD8EF20NP	20'
10"	CD10EF20NP	20'
12"	CD12EF20NP	10'/20'
15"	CD15EF20NP	10'/20'
18"	CD18EF20NP	11'/20'
24"	CD24EF20NP	11'/20'
30"	CD30EF20NP	11'/20'
36"	CD36EF20NP	11'/20'
42"	CD42EF20NP	11'/20'
48"	CD48EF20NP	11'/20'
60"	CD60EF20NP	11'/20'

**CorrDrain™ by CMF GLOBAL**

2445 Fenton Street ■ Chula Vista, CA 91914-3517 ■ Telephone: 619-869-8919 ■ Fax: 619-330-4532

1-877-586-6060 24 Hour Technical Hotline ■ 25 YEAR LIMITED SYSTEM WARRANTY

PRODUCT INSTALLATION TRAINING AVAILABLE



[www.corrdrain.com](http://www.corrdrain.com)